


IN-GROUND MOUNT



SURFACE MOUNT

## (or standard 4" sidewalk slab)

CAPACITY	2-4 Bikes
MATERIALS	1.5" OD 11 Gauge Tube. All open ends are capped to prevent moisture from entering. All welds are MIG welds around entire circumference of joined pieces.
FINISHES	<b>Galvanized</b> An after fabrication hot dipped galvanized finish is our standard option.
	<ul> <li>Powder Coat</li> <li>Our powder coat finish assures a high level of adhesion and durability by following these steps:</li> <li>1. Sandblast</li> <li>2. Epoxy primer electrostatically applied</li> <li>3. Final thick TGIC polyester powder coat</li> </ul>
	<b>Stainless</b> Stainless Steel: 304 grade stainless steel material finished in either a high polished shine or a satin finish.
MOUNT OPTIONS	<b>Surface</b> Each rack has two 2.5" x 6" mounting brackets double gusset welded to the "wheels". The brackets are 40" apart. Each bracket is anchored to the ground with two anchors. Anchors are included with each rack. Tamper-resistant fasteners are available upon request.
	<b>In-Ground</b> In-ground mount is embedded into concrete base. Specify

In-ground mount is embedded into concrete base. Specify in-ground mount for this option