


A bench may be mounted to the inside of the Pocket Shelter and still allow room for four bikes.



Dero Shelters can be used in a modular fashion (shared uprights). However, when used in this manner, please consult a Dero Bike Rack sales associate for layout, as the rack spacing and bike capacity can change!

CAPACITY

With Ultra Space Savers: 6 Bikes With Bike Files: 10 Bikes

MATERIALS

Uprights: 2" x 3/16" square tube

Feet: 3/8" plate

Horizontal members: 3/16" formed sheet

Roof panels: 26g type S deck or 1/4" polycarbonate

Roof members: 3/16" formed sheet **Side panels:** ¼" polycarbonate (optional)

FINISHES

Galvanized

An after fabrication hot dipped galvanized finish is our standard option.

Powder Coat

Our powder coat finish assures a high level of adhesion and durability by following these steps:

- 1. Sandblast
- 2. Epoxy primer electrostatically applied
- 3. Final thick TGIC polyester powder coat

MOUNT OPTIONS

Surface

Has four 6" square feet which must be anchored to the ground with supplied anchors.

3

LOAD DATA

Dead load: self weight of structure Live load: snow load = 45 psf Wind load: 90 mph exposure B Seismic load: moderate Footing: see page 4

Anchor bolt: Simpson strong-bolt 2, 1/2" x 5 1/2", 3 7/8"


minimum embed

ROOF OPTIONS

Galvanized S Deck

Polycarbonate Panel





The Pocket Shelter may be installed with Ultra Space Savers (left) or a Bike File (right)